

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

StoArmat Classic plus F/M/G



The Norwegian EPD Foundation

Owner of the declaration:

Sto SE & Co. KGaA

Product:

StoArmat Classic plus F/M/G

Declared unit:

1 kg

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR

IBU PCR Part B for coatings with organic binders

Program operator:

The Norwegian EPD Foundation

Declaration number:

NEPD-9449-9052

Registration number:

NEPD-9449-9052

Issue date:

24.03.2025

Valid to:

24.03.2030

EPD software:

LCAno EPD generator ID: 645566

General information

Product

StoArmat Classic plus F/M/G

Program operator:

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-norge.no

Declaration number:

NEPD-9449-9052

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
IBU PCR Part B for coatings with organic binders

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 kg StoArmat Classic plus F/M/G

Declared unit with option:

A1, A2, A3, A4, A5, C1, C2, C3, C4, D

Functional unit:

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Owner of the declaration:

Sto SE & Co. KGaA
Contact person: Linus Kaltenbach
Phone: +49 7744571010
e-mail: l.kaltenbach@sto.com

Manufacturer:

Sto SE & Co. KGaA
Ehrenbachstraße 1
79780 Stühlingen, Germany

Place of production:

Weizen
Ehrenbachstraße 1
79780 Stühlingen, Germany

Management system:

ISO 14001; ISO 50001; ISO 9001

Organisation no:

DE142834082

Issue date:

24.03.2025

Valid to:

24.03.2030

Year of study:

2023

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway. NEPDT143

Developer of EPD: Linus Kaltenbach

Reviewer of company-specific input data and EPD: Angelica Hultin

Approved:



Håkon Hauan, CEO EPD-Norge

Product

Product description:

StoArmat Classic plus F/M/G is an organic, cement-free reinforcing compound/base coat. It is composed of a polymer-dispersion binder, along with mineral fillers like marble granulate, water, and small quantities of additives. It can be used as a thin-layered reinforcing compound/base coat for selected facade systems such as StoTherm Classic® and StoVentec R and render systems for example StoRend. It also excels as a levelling filler or as a renovation filler on mineral and organic substrates on walls, ceilings and pillars in exterior. The application process can be done by machine or manually, using a rust-free steel trowel.

StoArmat Classic plus F/M/G has the following properties:

- base coat in accordance with EN 15824
- reaction to fire: class A2-s1, d0 in accordance with EN 13501-1, non-combustible
- cement-free
- ready-to-use
- resistant to cracking and mechanical stress

The three variants F/M/G differentiate in their appearance, due to the use of different texturing grain:

StoArmat Classic plus F for a fine-grained texture

StoArmat Classic plus M for a medium-grained texture

StoArmat Classic plus G for a coarse-grained texture

For the placing on the market of the product in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Regulation (EU) No. 305/2011 (CPR) applies. The product needs a declaration of performance taking into consideration EN 15824:2017 title and the CE-marking. For the application and use the respective national provisions apply.

Product specification

The following data is required by the corresponding PCR B. Further information can be found on the Safety Data Sheet on www.sto.de.

1) This product contains substances listed in the candidate list (date: 12.03.2025) exceeding 0.1 percentage by mass: no.

2) This product contains other CMR substances in categories 1A or 1B which are not on the candidate list, exceeding 0.1 percentage by mass: no

3) Biocide products were added to this construction product or it has been treated with biocide products (this then concerns a treated product as defined by the (EU) Ordinance on Biocide Products No. 528/2012): yes
1,2-Benzisothiazol-3(2H)-on; in-can preservative; $\geq 0,0025$ - $<0,025$
CAS-nr.: 2634-33-5

reaction mass of
5-Chlor-2-methyl-4-isothiazolin-3-on and
2-Methyl-2Hisothiazol-3-on (3:1) in-can preservative; $= < 0,0002$
CAS-nr.: 55965-84-9

Materials	Value	Unit
Filler	> 70	%
Binder	10 - 20	%
Water	10 - 20	%
Additive	1 - 2	%

Technical data:

The technical data stated here is relevant for the use of the declared product. Further information regarding the technical properties can be found on the Technical Data Sheet on www.sto.de.

Criterion	Standard/test specification	Class
Density	EN ISO 2811	1.50 - 1.70 g/cm ³
Water permeability rate w	EN 1062-3	W3 low
Water vapour diffusion-equivalent air layer thickness μ	EN ISO 7783	V2 medium
Reaction to fire	DIN 13501-1	A2-s1, d0

Market:

The main markets are Germany, Switzerland, Austria, France, Belgium, Netherlands and Sweden.

Reference service life, product

The service life of StoArmat Classic plus F/M/G is 40 years in accordance with the BBSR table "Service lives of components for life cycle assessment according to BNB" in exterior application. Experience shows that if used as intended and installed correctly, the working life of reinforcing compound is 50 years and longer.

A reference service life (RSL) in accordance with ISO 15686-1,-2,-7, and -8 is not declared.

Reference service life, building or construction works

LCA: Calculation rules

Declared unit:

1 kg StoArmat Classic plus F/M/G

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.


Materials	Source	Data quality	Year
Additives	CEPE RM Database v3.0	Database	2016
Additives	CEPE RM Database v3.0, ecoinvent 3.6	Database	2016
Additives	ecoinvent 3.6	Database	2019
Binders and Resins	CEPE RM Database v3.0	Database	2016
Chemical	ecoinvent 3.6	Database	2019
Fillers	ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Packaging - Wood	Modified ecoinvent 3.6	Database	2019
Pigments and Fillers	CEPE RM Database v3.0	Database	2016
Solvent	CEPE RM Database v3.0	Database	2016
Water	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage								End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use		De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7		C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND		X	X	X	X	X

System boundary:

The scope of this LCA is cradle to gate with options, modules C1-C4 and module D. No actions are to be taken during User stage.



Additional technical information:

Reinforcing compound is categorized under the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" and is categorized as non-hazardous waste.

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

A1-A3 (Manufacturing of the product): The raw materials are produced by and transported from suppliers located in Europe. The raw materials are filled in weighting containers and thereafter mixed together. Quality control checks the consistency of the product and adjusts if necessary. The finished product is filled into pails and stored. The product is transported on pallets and delivered to customers in Europe with focus on Germany.

A4 (Transport to market/building site): Since the distance to the construction site can vary strongly, a distance of 100 km is used to allow simple scaling for individual projects.

A5 (Installation): The product is applied according to the specification in the technical data sheet at the building site. Installation is generally done manually. Outputs are small amounts of waste from the product itself (assumed to be a maximum of 3%) and waste from packaging materials.

C1 (De-construction, demolition): It is assumed that StoArmat Classic plus F/M/G is dismantled using machinery.

C2 (Transport end of life): This stage includes the transportation effects of demolished waste to a waste processing area. The distance between the demolishing area and a waste processing area is assumed to be quite short (less than 100 km). The distance varies depending on the type of waste processing.

C3, C4 (Waste processing): Reinforcing compound is not classified as hazardous waste and treated as mixed construction waste. A typical End of life scenario for construction waste in Germany is a mix of recycling and landfill. Since a 100% End-of-life scenario has to be declared according to the PCR, it is assumed as 100% landfill

D (Environmental costs and benefits of recycling and reuse): Energy credit related to energy recovery from the incineration is included in module D.

Stages not included:

Once installation is complete, no actions or technical operations are required during the use stage until the end of life stage. Stages B1-B7 are therefore not declared.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (kgkm)	36,7 %	105	0,043	l/tkm	4,51
Assembly (A5)	Unit	Value			
Material loss, including waste treatment (psc)	Units	0,030			
Waste, packaging, pallet, EUR wooden pallet, reusable, average treatment (kg)	kg	0,033			
Waste, packaging, polyethylene, PE plastic parts, to average treatment (kg)	kg	0,016			
De-construction demolition (C1)	Unit	Value			
Electricity, Germany (kWh)	kWh	0,013			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (kgkm)	36,7 %	100	0,043	l/tkm	4,30
Disposal (C4)	Unit	Value			
Waste, inert waste, to landfill (kg)	kg	1.00			
Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of electricity (MJ)	MJ	0,0011			
Substitution of thermal energy, district heating (MJ)	MJ	0,017			
Substitution of electricity, in Norway (MJ)	MJ	0,00010			
Substitution of thermal energy, district heating, in Norway (MJ)	MJ	0,0015			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact												
Indicator	Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D	
 GWP-total	kg CO ₂ -eq	4,94E-01	1,07E-02	8,16E-03	1,80E-02	5,14E-02	7,62E-03	1,72E-02	0	8,22E-03	-1,13E-04	
 GWP-fossil	kg CO ₂ -eq	5,44E-01	1,07E-02	6,57E-03	1,80E-02	1,37E-03	7,48E-03	1,71E-02	0	8,20E-03	-1,09E-04	
 GWP-biogenic	kg CO ₂ -eq	-4,96E-02	4,43E-06	7,17E-04	7,45E-06	5,00E-02	1,26E-04	7,10E-06	0	9,58E-06	-2,25E-07	
 GWP-luluc	kg CO ₂ -eq	8,34E-05	3,81E-06	8,76E-04	6,41E-06	1,13E-07	9,07E-06	6,10E-06	0	2,02E-06	-3,76E-06	
 ODP	kg CFC 11 -eq	3,69E-08	2,43E-09	5,58E-10	4,08E-09	8,60E-11	2,93E-10	3,88E-09	0	3,11E-09	-7,95E-06	
 AP	mol H ⁺ -eq	2,75E-03	3,08E-05	8,12E-06	5,17E-05	1,99E-06	2,17E-05	4,93E-05	0	7,30E-05	-8,98E-07	
 EP-FreshWater	kg P -eq	4,81E-05	8,56E-08	3,65E-08	1,44E-07	3,25E-09	1,13E-06	1,37E-07	0	9,30E-08	-9,69E-09	
 EP-Marine	kg N -eq	4,66E-04	6,09E-06	2,77E-06	1,02E-05	1,64E-06	3,36E-06	9,75E-06	0	2,71E-05	-2,94E-07	
 EP-Terrestrial	mol N -eq	4,85E-03	6,81E-05	2,09E-05	1,14E-04	7,48E-06	5,32E-05	1,09E-04	0	2,99E-04	-3,18E-06	
 POCP	kg NMVOC -eq	1,61E-03	2,61E-05	6,47E-06	4,39E-05	2,34E-06	1,01E-05	4,18E-05	0	8,56E-05	-8,76E-07	
 ADP-minerals&metals ¹	kg Sb -eq	2,47E-06	2,96E-07	4,10E-08	4,97E-07	7,75E-09	6,22E-08	4,74E-07	0	7,39E-08	-1,08E-09	
 ADP-fossil ¹	MJ	8,54E+00	1,62E-01	6,18E-02	2,72E-01	5,97E-03	1,02E-01	2,59E-01	0	2,26E-01	-1,56E-03	
 WDP ¹	m ³	2,10E+01	1,57E-01	7,59E+00	2,63E-01	2,01E-02	1,03E+00	2,51E-01	0	1,39E+00	-1,94E-02	

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

Additional environmental impact indicators

Indicator	Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
 PM	Disease incidence	8,70E-07	6,56E-10	5,40E-11	1,10E-09	3,30E-11	8,40E-11	1,05E-09	0	1,56E-09	-5,40E-11
 IRP ²	kgBq U235 -eq	1,04E+02	7,08E-04	4,29E-05	1,19E-03	2,65E-05	3,20E-04	1,13E-03	0	1,03E-03	-9,96E-06
 ETP-fw ¹	CTUe	7,37E+00	1,20E-01	4,43E-02	2,02E-01	5,79E-03	8,69E-02	1,92E-01	0	1,23E-01	-8,48E-03
 HTP-c ¹	CTUh	8,22E-10	0,00E+00	2,00E-12	0,00E+00	0,00E+00	2,00E-12	0,00E+00	0	5,00E-12	0,00E+00
 HTP-nc ¹	CTUh	3,88E-08	1,30E-10	6,20E-11	2,20E-10	8,00E-12	8,70E-11	2,10E-10	0	8,90E-11	-9,00E-12
 SQP ¹	dimensionless	2,46E+00	1,13E-01	-1,94E-02	1,90E-01	9,80E-03	2,41E-02	1,81E-01	0	8,69E-01	-1,04E-02

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use												
Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	PERE	MJ	9,09E-01	2,32E-03	8,56E-02	3,90E-03	1,48E-04	1,85E-02	3,71E-03	0	8,08E-03	-9,63E-03
	PERM	MJ	4,58E-01	0,00E+00	0,00E+00	0,00E+00	-4,58E-01	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00
	PERT	MJ	1,37E+00	2,32E-03	8,56E-02	3,90E-03	-4,58E-01	1,85E-02	3,71E-03	0	8,08E-03	-9,63E-03
	PENRE	MJ	8,94E+00	1,62E-01	6,18E-02	2,72E-01	5,97E-03	1,02E-01	2,59E-01	0	2,26E-01	-1,56E-03
	PENRM	MJ	7,08E-01	0,00E+00	0,00E+00	0,00E+00	-7,08E-01	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00
	PENRT	MJ	9,65E+00	1,62E-01	6,18E-02	2,72E-01	-7,02E-01	1,02E-01	2,59E-01	0	2,26E-01	-1,56E-03
	SM	kg	1,74E-04	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00
	RSF	MJ	5,73E-03	8,29E-05	1,80E-05	1,39E-04	3,92E-06	5,78E-03	1,33E-04	0	1,68E-04	-1,69E-06
	NRSF	MJ	1,60E-03	2,97E-04	2,38E-05	4,98E-04	1,30E-05	1,87E-05	4,75E-04	0	3,62E-04	-5,71E-04
	FW	m ³	3,52E-01	1,73E-05	6,66E-04	2,91E-05	3,26E-06	4,63E-05	2,77E-05	0	2,78E-04	-1,16E-05

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

*Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

End of life - Waste												
Indicator	Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D	
	HWD	kg	3,82E-03	8,35E-06	1,04E-03	1,40E-05	0,00E+00	1,01E-05	1,34E-05	0	0,00E+00	-7,33E-08
	NHWD	kg	1,84E+00	7,88E-03	1,55E-03	1,32E-02	1,83E-02	4,28E-04	1,26E-02	0	1,00E+00	-3,68E-05
	RWD	kg	1,48E-05	1,10E-06	5,93E-08	1,85E-06	0,00E+00	4,11E-07	1,77E-06	0	0,00E+00	-8,17E-09

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

End of life - Output flow												
Indicator	Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D	
	CRU	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,14E-02	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00
	MFR	kg	0,00E+00	0,00E+00	6,19E-04	0,00E+00	8,52E-03	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00
	MER	kg	0,00E+00	0,00E+00	4,81E-03	0,00E+00	1,64E-03	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00
	EEE	MJ	0,00E+00	0,00E+00	2,93E-03	0,00E+00	1,24E-03	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00
	EET	MJ	0,00E+00	0,00E+00	4,43E-02	0,00E+00	1,88E-02	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0,00E+00
Biogenic carbon content in accompanying packaging	kg C	1,36E-02

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, low voltage, 100% hydro, certificate, 01.01.2023-31.12.2023, Germany (kWh)	Modified ecoinvent 3.6	60,95	g CO ₂ -eq/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Not relevant

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products											
Indicator	Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	5,41E-01	1,07E-02	8,00E-03	1,80E-02	1,37E-03	8,19E-03	1,72E-02	0	8,21E-03	-1,11E-04

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21

Ruud and Iversen (2023) EPD generator for PCR IBU Part B: Requirements on the EPD for Coatings with organic binders, LCA.no report number: 13.23

NPCR Part A: Construction products and services. Ver. 2.0. April 2021, EPD-Norge.

IBU PCR Part B: Requirements on the EPD for Coatings with organic binders, version 4, 2023, IBU - Institut Bauen und Umwelt e.V.

 Global program operator	Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-norge.no
 Building with conscience.	Owner of the declaration: Sto SE & Co. KGaA Ehrenbachstraße 1, 79780 Stühlingen, Germany	Phone: +49 7744571010 e-mail: l.kaltenbach@sto.com web: https://www.sto.com/
	Author of the Life Cycle Assessment LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal